

Typical Applications

GK-Oil&Grease™ is an environmentally friendly formula.

GK-Oil&Grease™ cleans petroleum based materials from virtually all surfaces regardless of the application and can also be used to clean embedded organic food stains outdoors around garbage collection areas, food service and outside eating areas.

- **Hard Surface Cleaning** - Concrete, Concrete Pavers, Asphalt: Dampen the contaminated surface, apply GK-Oil&Grease™, scrub with broom or brush and allow it to work for 20-30 min. Then rinse or power wash or leave overnight to dry, if conditions permit. Best results are obtained when the product is allowed to air dry without rinsing. Keep the work-site damp during treatment and repeat as necessary. Older stains may require multiple applications. GK-Oil&Grease™ is also effective in cleaning small gasoline spills on hard surfaces.
- **Porous Surface Cleaning** Stains & Soils: Scrape surface, rinse area of loose dirt, dampen and apply product. Scrub surface stains with broom or brush, keep damp for 20-30 minutes. For best results allow the applicated areas to air dry without rinsing.
- **Recommended Application for Heavy and General Equipment Cleaning** - Do not pre-wet surfaces or use in direct sunlight on painted surfaces. A 1:3 dilution is recommended for most applications with a maximum recommended dilution of 1:4.
- **Pressure Washing/Degreasing** - Pressure blast heavy materials. Spray surface with 50/50 solution and pressure wash again from bottom up. Do not allow surfaces to dry.
- **Floor Machines** - Depending upon the severity of the floor stains, a 1:3 dilution with water is recommended to start with. Once floor is clean, the dilution can be increased to 1:4.
- **Precautions and Limitations** - Wear protective clothing (rubber gloves, eye protections). Pre-test new finishes by applying to a small area first. Best results are seen when applied to damp concrete surfaces.

Directions For Use

Please follow good safety precautions and keep this product and all cleaning products out of the reach of children and pets. Store in a cool, dry place. Avoid contact with eyes. Wash hands after use. All cleaning products should be used in accordance with State and Local regulations.

Can be diluted with water between 1:2 for heavier loads & stains, up to 1:4 for lighter applications. Use scrub brush to facilitate cleaning. Do not store diluted product for later use. When used outdoors, temperature should be above 55° for best results.

GEOKLEEN™
THE NATURAL SOLUTION



GK Oil & Grease™

BIOENZYMATIC CLEANER

From the GeoKleen family of products.

BIODEGRADABLE

Hard Surface Cleaner And Biostimulant For Industrial Floors And Heavy Equipment

*Designed for Industrial and Commercial Applications
Quick Acting and Effective in Removing Surface Stains*

Features

- Inoculates contaminations with bacteria.
- Cleans surfaces of oil spills and stains.
- Cleans oily equipment, vehicles and tools.
- Cleans small gasoline spills on hard surfaces.
- Contains no petroleum distillates or solvents.
- Cleans embedded organic food stains.
- Contains essential microbial nutrients.
- Enhances biodegradation above and below ground surface when used as recommended.
- No rinsing is required except on painted metal surfaces.


Caution: Eye Irritant

Avoid contact with eyes, open cuts or sores. In case of eye contact, flush eyes with water for 15 minutes. Avoid inhalation. If swallowed watch victim for any sign of illness. Call a physician. Induce vomiting only if advised by a physician. Wash hands after use. Do not use this container for storing beverages or other liquids. This product contains non-pathogenic bacteria.

GEOKLEEN™
THE NATURAL SOLUTION

Questions? Contact:

GEOKLEEN, Inc.
580 S. Salina Street
Syracuse, NY 13202
Phone: 315.701.4439
In the U.S.: 800.651.1919
Fax: 315.422.4867
www.geokleen.com



1 US GAL.

Made In The USA